

ES2000

Flame-Retardant, High-Shrink-Ratio,
Adhesive-Lined Semirigid Polyolefin Tubing

PRODUCT FACTS

- 4:1 shrink ratio allows a few sizes to cover a wide range of splice and component diameters
- Flame-retardant and mechanically tough, the tubing provides strain relief and abrasion protection of wire splices, terminals, and other components
- Thick adhesive liner forms an effective barrier against fluids and moisture and performs well at an extended temperature range
- UL recognized
- RoHS compliant

APPLICATIONS

Specially designed for environmental sealing and electrical insulation of wire splices, terminations, and components.


INSTALLATION

Minimum shrink temperature: 100°C [212°F]
Minimum full recovery temperature: 135°C [275°F]

OPERATING TEMPERATURE RANGE

-40°C to 105°C [-40°F to 221°F]

Specifications/Approvals

Series	UL* 	Raychem
ES2000	E85381 600 V, 125°C	RT-1112

Product Dimensions

Part Number	Inside Diameter (Including Core)		Recovered Wall Thickness*		
	Minimum Expanded as Supplied	Maximum Recovered After Heating	Minimum Total Wall After Heating	Minimum Jacket Wall After Heating	Minimum Adhesive Wall After Heating
ES2000-No.1	5.72 [0.225]	1.27 [0.050]	1.20 [0.047]	0.64 [0.025]	0.56 [0.022]
ES2000-No.2	7.44 [0.293]	1.65 [0.065]	1.52 [0.060]	0.76 [0.030]	0.76 [0.030]
ES2000-No.3	10.85 [0.427]	2.41 [0.095]	1.91 [0.075]	0.89 [0.035]	1.02 [0.040]
ES2000-No.4	17.78 [0.700]	4.45 [0.175]	2.41 [0.095]	1.04 [0.041]	1.37 [0.054]

*Wall thickness will be less if tubing recovery is restricted during shrinkage.

Ordering Information

Color	Standard	Black (-0)
Size selection	Always order the largest size that will shrink snugly over the component to be covered.	
Standard packaging	Cut pieces.	
Marking	Tubing will be printed with its numbered size (such as ES-1, ES-2, ES-3, or ES-4).	
Ordering description	Specify product name, numbered size, color, and cut length (for example, ES2000-NO. 2-0-50MM).	



Authorised Reseller

CONTACT MAJOR PRODUCT STOCKIST:



Electro-Power and Data Equipment Pty Ltd

Phone 1300 361 003

Phone Intl + 61 3 5374 0980 • Fax +61 3 5374 0989 • Nat 1300 134 416 • Email epde@epde.com.au • Web www.epde.com.au